Datenblatt

NodeMCU v3 - ESP8266 Development Board, CH340G



Order number:	NMCUV3
Hersteller:	BerryBase
EAN:	4251266702061
Herkunftsland:	China
Zolltarifnummer:	85269200
Gewicht:	0.01 kg

Das NodeMcu ist ein Open-Source-Firmware- und Entwicklungskit, mit dem Sie Ihr IOT-Produkt innerhalb weniger Lua-Skriptzeilen prototypisieren können.

Eigenschaften:

- Open Source
- Interaktiv
- Programmierbar
- Kostengünstig
- Einfach
- Smart
- WI-FI möglich
- Breadboard-freundlich

Spezifikation:

- Das auf ESP8266 basierende Development Kit vereint GPIO, PWM, IIC, 1-Wire und ADC auf einer Platine.
- Beschleunigen Sie Ihre Entwicklung auf schnellste Weise mit der NodeMCU-Firmware! USB-TTL enthalten
- Plug & Play 10 GPIO,
- jeder GPIO kann PWM
- I2C, 1-Draht PCB Antenne
- 2 neue PINs: Ground und USB Power Output
- CH340G USB Chipsatz
- Abmessungen: ca. 60 x 31 x 13 mm

Technische Details:

- Controller: ESP8266
- Anschluss: Micro-USB
- CPU: 80 MHz, 32Bit RISC

All names and signs listed here are the property of the respective manufacturer. Misprints, changes & errors reserved.

- RAM: 96kB
- Flash: 4 MB
- WiFi (Client, AccessPoint Mode)
- 10 digital IOPins, 1 ADC (10Bit)
- Integrierte WLAN Antenne
- Gewicht: 10g

Weitere Bilder:

All names and signs listed here are the property of the respective manufacturer. Misprints, changes & errors reserved.